

<b>Part Number</b>	INT13-TGG 0B 307 CLADXXZ	
<b>Size/Series</b>	0B (Metal (Mechanical Keying))	
<b>MECHANICAL DETAILS</b>		
<b>Shell Style/Model</b>	Straight plug,cable collet	
<b>Keying</b>	1 key (alpha=0,plug: male contacts,receptacle: female contacts)	
<b>Housing Material</b>	Brass (chrome plated) shell and collet nut,nickel plated brass latch sleeve and mid pieces.	
<b>Cable Fixing</b>	3.0 - 5 mm (0.11 - 0.2")	
<b>Variant</b>	None	
<b>PERFORMANCE DETAILS</b>		
<b>Insert</b>	7 Low Voltage	
<b>Configuration</b>	Brass (gold plated)	
<b>Insulator</b>	P: PPS	
<b>Specifications</b>	Low Voltage	Contact Type: Solder
		Max. Matings: 5000
		Contact Dia.: 0.5 mm (0.02")
		Bucket Dia.: 0.45 mm (0.018")

		Max. Solid Conductor: 0.09 mm <sup>2</sup> (AWG 28)
		Max. Stranded Conductor: 0.09 mm <sup>2</sup> (AWG 28)
		R (max): 10 mOhm
		Vtest (contact-shell): 700 V
		Vtest (contact-contact): 800 V
		Rated Current: 2.5A (AC/DC)
<b>OTHER CHARACTERISTICS</b>		
<b>Endurance (Shell):</b>	5000 mating cycles	
Temp (min)	-40 deg	
Temp (max):	200 deg C	
Humidity (max):	<=95% [at 60 deg C / 140 F]	
Vibration	15 g [10 Hz - 2000 Hz]	
Shock Resistance	100 g [ 6 ms]	
Salt Spray Corrosion	>144 hr	
IP Rating	50	
Shielding (min):	75 dB (10 MHz)	
Shielding (min):	40 dB (1 GHz)	
P op (max):	60 bar (870 psi)	