

Part Number	INT13-ZGG 0B 305	
Size/Series	0B (Metal (Mechanical Keying))	
MECHANICAL DETAILS		
Shell Style/Model	Fixed receptacle, nut fixing	
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)	
Housing Material	Brass (chrome plated) shell and nut	
Cable Fixing	None	
Variant	None	
PERFORMANCE DETAILS		
Insert	5 Low Voltage	
Configuration	Brass (gold plated)	
Insulator	P: PPS	
Specifications	Low Voltage	Contact Type: Solder or PCB
		Contact Dia.: 0.7 mm (0.028")
		Bucket Dia.: 0.8 mm (0.031")

		Max. Solid Conductor: 0.34 mm ² (AWG 22)
		Max. Stranded Conductor: 0.34 mm ² (AWG 22)
		R (max): 6.1 mOhm
		Vtest (contact-shell): 700 V
		Vtest (contact-contact): 1000 V
		Rated Current: 6.5 A (AC/DC)
OTHER CHARACTERISTICS		
Endurance (Shell):		6000 mating cycles
Temp (min)		-40 °C
Temp (max):		250 °C
Humidity (max):		<=95% [at 60 deg C / 140 F]
Vibration		15 g [10 Hz - 2000 Hz]
Shock Resistance		100 g [6 ms]
Salt Spray Corrosion		>144 hr
IP Rating		50
Shielding (min):		75 dB (10 MHz)
Shielding (min):		40 dB (1 GHz)
P op (max):		60 bar (870 psi)